

### Product Description and Application

Mobil Delvac 1300 Series oils are a range of high quality severe service engine oils made from solvent refined paraffinic base oils fortified with detergent/dispersant, anti-wear and pour point depressant additives.

They are recommended for turbo-charged and naturally aspirated diesel engines operating under severe conditions in both off highway plant and road fleet operation. They are also suitable for petrol engines.

In the relevant viscosities, they may be used in applications requiring products approved against Allison C-4 specification.

### Specifications

Mobil Delvac 1300 Series oils are available in SAE 10W, 20W-20, 30 and 40 and meet the following specifications :

- API CF/SF

Suitable for use in Mercedes-Benz Sheet 227.0 applications ( Delvac 1310, 1330 & 1340)  
Allison C-4 quality level ( Delvac 1310 & Delvac 1330 )

### Benefits

Mobil Delvac 1300 Series oils offer the following benefits :

- Wide application range in both contractor and heavy duty transport type operations
- Lower operating costs from cleaner engines, less wear and longer engine service life
- Continuous maximum engine output due to freedom from ring sticking, reduced deposits, long valve life, reduced wear of cylinders, valve train and bearings and good control over low temperature sludge
- Lower operating costs and improved vehicle and plant utilisation lead to higher operating profit

## Health and Safety

Based on available toxicological information, it has been determined that these products pose no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

## Typical Characteristics

---

<b>Mobil Delvac</b>	<b>1310</b>	<b>1320</b>	<b>1330</b>	<b>1340</b>
SAE No.	10W	20W-20	30	40
Viscosity, cSt at 40°C	40	60	95	140
Viscosity, cSt at 100°C	5.6/5.9	8.0/9.2	10.8/11.9	13.5/15.2
Viscosity Index min.	100	95	95	95
TBN - ASTM 2876	7.2	7.2	7.2	7.2
Pour Point, °C max.	-33	-21	-18	-12

---

Due to continual product research and development, the information contained herein is subject to change without notice.

---

**Mobil Oil Company Limited**  
**Acting as Agent for Mobil Lubricants UK Limited**  
**ExxonMobil House, Ermyn Way**  
**Leatherhead, Surrey, KT22 8UX**  
**Telephone: 01372 22 2000**

