

Product Data Sheet

Mobil Extra 4T High Performance Semi-Synthetic 4Stroke Motorcycle engine Oil

Product Description and Application

Mobil Extra 4T is an SAE 10W-40 product formulated with a precise balance of high quality mineral and special hydro-processed base stocks combined with the most modern dispersant-detergents, anti-oxidants, anti-wear agents and corrosion inhibitors to provide superior engine lubrication and overall protection in all seasons. Mobil Extra 4T also contains a special viscosity index improver with excellent shear stability properties.

Mobil Extra 4T is a high performance multigrade engine oil designed to satisfy the most severe performance requirements of today's 4 stroke engine motorcycles.

Benefits

Mobil Extra 4T offers the following benefits:

- Excellent low temperature cranking and pumping properties provide faster, easier starting, even in severe winter conditions
- Good thermal stability in all engines even at high revs
- Elimination of ash deposits on piston crowns and valves
- Also suitable for machines fitted with wet clutches

Specifications

Mobil Extra 4T is accredited to the following specifications :

- ACEA A3-96/B3-96
- API SH/CD
- API SJ/CF

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

Mobil Extra 4T

| | |
|-------------------------------|---------|
| SAE No. | 10W-40 |
| Viscosity, cSt at 40°C | 98 |
| Viscosity, cSt at 100°C | 14.5 |
| CCS Viscosity at -20°C, Poise | 35 max. |
| Viscosity Index | 155 |
| TBN (ASTM D2896), mg KOH/g | 10 |
| Sulphated Ash, % wt | 1.1 |
| Pour Point, °C | -33 |
| Flash Point, °C COC | 218 |

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

