

Product Data Sheet

Mobil Formrex 8077 Special Purpose Mould Release Oil

Product Description

A high quality, light coloured mould release oil possessing good resistance to oxidation and good thermal stability properties.

Benefits

Clean and effective release with minimum retardation.

Application

Mobil Formrex 8077 has been specifically developed for use as a mould release agent. Can be best applied by spray but other methods can be used avoiding excess application. This product is particularly suitable for use with steel moulds.

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

Mobil Formrex 8077

Density, kg/m ³ at 15°C	0.875
Viscosity, cSt at 40°C	31
Viscosity, cSt at 100°C	5.2
Viscosity Index typical	99
Pour Point, °C max.	-12
Flash Point, °C	202
Colour ISO 2049	1.0

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

