

### Product Description and Application

Mobil Super Diesel 15W-40 is a premium multigrade engine oil designed to satisfy the service requirements of modern diesel and petrol engine passenger cars, including those fitted with turbo-charged engines.

It is formulated with a solvent refined paraffinic base oil blended with a special Viscosity Index Improver which provides excellent viscosity retention. It also contains detergent/dispersant, anti-wear and anti-corrosive additives which are balanced to provide superior engine lubrication protection.

Mobil Super Diesel 15W-40 is recommended for use in diesel and petrol fuelled passenger cars, including those fitted with turbo-charged engines.

### Benefits

Mobil Super Diesel 15W-40 offers the following benefits:

- Recommended for all diesel and petrol passenger car engines including turbo-charged engines
- Suitable for all driving conditions providing superior soot and deposit control
- Exceeds car manufacturers' standards for quality and performance
- Provides longer engine life with lower operating costs and longer periods between overhauls
- Reduces black sludge tendency, and provides excellent oxidation protection with superior anti-wear properties

### Specifications

Mobil Super Diesel 15W-40 is accredited to the following specifications:

- ACEA B3 / A3
- API CF/SJ, SH/CD
- JASO
- Mercedes Benz 229.1

## Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

## Typical Characteristics

---

### Mobil Super Diesel 15W-40

SAE No.	15W-40
Viscosity, cSt at 40°C	104
Viscosity, cSt at 100°C	14.4
CCS, Viscosity Poises, at -15°C	32
Viscosity Index	136
T.B.N. - ASTM D2896	10.4
Sulphated Ash, % wt	1.1
Relative Density 15/4°C	0.880
Pour Point, °C	-27
Flash Point ,COC °C	226

---

Due to continual product research and development, the information contained herein is subject to change without notice.

---

**Mobil Oil Company Limited**  
**Acting as Agent for Mobil Lubricants UK Limited**  
**ExxonMobil House, Ermyn Way**  
**Leatherhead, Surrey, KT22 8UX**  
**Telephone: 01372 22 2000**

