

Product Data Sheet

Mobil Super S 15W-40 High Performance Semi-synthetic Multigrade Engine Oil

Product Description and Application

Mobil Super S 15W-40 is an extra high performance semi-synthetic motor oil designed to provide outstanding protection for the engines of all gasoline and diesel-powered passenger cars, light trucks and vans. It is particularly suitable for high performance engines, especially those fitted with turbo-chargers and exceeds the engine oil performance requirements of all major car manufacturers.

Using proven Mobil synthetic engine oil technology, Mobil Super S 15W-40 offers benefits beyond that of conventional mineral-based products. These include excellent low temperature fluidity to ensure easy starting in cold weather and low volatility that helps reduce oil consumption. Coupled with a superior additive system, the Mobil Super S formulation provides exceptional engine cleanliness and wear protection even under severe operating conditions.

Mobil Super S 15W-40 is recommended for use in all modern passenger car gasoline and diesel engines, including turbo-charged models. It is also suitable for all light duty trucks and vans.

Mobil Super S 15W-40 is recommended for use under the most severe operating conditions where oils offering superior performance are required.

Benefits

Mobil Super S 15W-40 offers the following benefits:

- Superior to mineral oils
- Outstanding engine cleanliness and anti-wear properties leading to longer engine life
- Easier starting at low temperatures
- Excellent high temperature properties
- Low oil consumption
- Turbo-proven dependability
- Helps lower emissions
- Ideal for all driving conditions
- For all gasoline and diesel engines with or without turbo or catalytic converter

Specifications

Mobil Super S 15W-40 meets or surpasses the following specifications:

- ACEA A3-98 / B3-98
- API SJ/CF
- Mercedes Benz 229.1
- VW 501.00 / VW 505.00 approved

It also meets the European CCMC G4/PD2 requirements which are now obsolete.

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

	Mobil Super S 15W-40
SAE No.	15W-40
Viscosity, cSt at 40°C	106
Viscosity, cSt at 100°C	14.4
CCS Viscosity at -20°C, Poises	35 max.
Viscosity Index	134
TBN (ASTM D2896), mg KOH/g	10
Sulphated Ash, %wt	1.3
Pour Point, °C	-33
Flash Point, °C	226

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

