

Mobil Antifreeze

Description

- Concentrated antifreeze formula.
- Contains Mono Ethylene Glycol. Helps to prevent winter freezing and summer overheating.
- Three years protection
- Meets exacting quality standard BS6580-1992.
- Mobil Antifreeze should not be mixed with silicate free, OAT engine coolants.



Product Directions

Mobil Antifreeze must be diluted with water before use. It is hard water compatible and can be mixed with tap water before filling into the cooling system.

Dilution chart

Antifreeze	Water	Freeze protection
12%	88%	-5°C
25%	75%	-12°C
33%	67%	-18°C
50%	50%	-38°C
60%	40%	-62°C

For preparation of the coolant use clean, not overly hard water. Waste from mining, sea water, brackish water, brine, industrial waste water are all unsuitable.

Water hardness	0 to 20 °dGH (0 - 3.6 mmol/l)
Chloride content	max. 100 ppm
Sulphate content	max. 100 ppm

Technical Specifications

Colour	blue
Density at 20 °C	1.13 g/cm ³
Boiling point	≥ 165 °C
Flash point	> 115 °C
pH value	7.7
Reserve alkalinity: M/10 HCl	21 ml
Water content	max. 5 %

Pack sizes :

- 1l, 5l, 20l & 208l

