

Mobil Delvac Super 1400 15W-40

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 1400 15W-40 is a high performance diesel engine oil that provides proven protection of diesel engines operating on and off-highway severe service applications. Mobil Delvac Super 1400 15W-40 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features & Benefits

The technology in Mobil Delvac Super 1400 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

Applications

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture



Specifications & Approvals

Mobil Delvac Super 1400 15W-40 meets or exceeds the following industry specifications	15W-40
ACEA E3/B3/B4/A3	X
API CG-4/CF/SJ	X

Mobil Delvac Super 1400 15W-40 has the following builder approvals	15W-40
MB 228.3	X
MAN 3275	X
Volvo VDS-2	X
MTU Type 2	X

Typical Properties

Mobil Delvac Super 1400 15W-40	
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	106
cSt @ 100°C	15.0
Viscosity Index, ASTM D 2270	135
Sulfated Ash, wt%, ASTM D 874	1,4
Total Base #, mg KOH/g, ASTM D 2896	11,5
Pour Point, °C, ASTM D 97	-27
Flash Point, °C, ASTM D 92	220
Density @15 °C kg/l, ASTM D 4052	0.887

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, Delvac (and any other trademarks) are trademarks of Exxon Mobil Corporation, or one of its subsidiaries

