

Mobil Super M 10W-40 and 15W-40

High Performance Multi-grade Passenger Vehicle Engine Oils

Product Description

Mobil Super M 10W-40 and 15W-40 are premium performance conventional oils that exceed the latest industry standards required in today's gasoline and diesel automobile engines.

Features & Benefits

Mobil Super M 10W-40 and 15W-40 keep engines running cleanly, smoothly and protects through a combination of high quality conventional mineral oils and a premium performance additive system. Mobil Super M 10W-40 and 15W-40 maintains overall engine cleanliness, preventing the build up of harmful deposits, sludge and varnish; and fight wear and corrosion under a variety of driving conditions. Key features and benefits:

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Reduced engine deposits, build-up of harmful sludge and deposit produced in the hot zones within an engines
Friction fighting anti-wear system	Reduced wear which can lead to lower maintenance costs
Cleaning agents	Clean running engine leading to longer engine life and more reliable operation
High Viscosity Index and Shear Stability	Improved lubrication at normal and high temperatures Excellent high and low temperature protection in severe driving conditions

Applications

Mobil Super M 10W-40 and 15W-40 are specifically recommended for use in all types of vehicles Mobil Super M 10W-40 and 15W-40 are excellent choices for passenger cars, light trucks and vans.



Specifications & Approvals

Mobil Super M meets or exceeds the following industry specifications:	10W-40	15W-40
ACEA	A2,B2, A3, B3	A2,B2, A3, B3
API	SL,SJ,CF	SL,SJ,CF

Mobil Super M has the following builder approvals:	10W-40	15W-40
MB	229.1	229.1
VW	505.00	505.00

Mobil Super M is recommended for use in applications requiring:	10W-40	15W-40
VW		501.01

Typical Properties

Mobil Super M	10W-40	15W-40
SAE Grade	10W-40	15W-40
Viscosity, ASTM D 445		
cSt @ 40°C	98	107
cSt @ 100°C	14.4	14.4
Viscosity Index, ASTM D 2270	157	141
Sulphated Ash, wt%, ASTM D 874	0.91	0.91
HTHS Viscosity, mPa.s @ 150°C, ASTM D4683	3.95	4.00
Pour Point, °C, ASTM D 97	-30	-24
Flash Point, °C, ASTM D 92	230	230
Density @ 15°C, kg/l, ASTM D 4052	0.870	0.885

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus and Super M are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

