



Mobil Delvac Super Multigrades

Heavy Duty Engine Oils

Product Description

Mobil Delvac Super 10W-30, 15W-40 and 20W-50 are high performance, heavy duty engine oils that provide proven protection to diesel engines operating in severe on and off-highway service applications. Mobil Delvac Super Multigrade engine oils are recommended for use in a wide range of heavy duty applications and operating environments found in the trucking, construction, and agricultural industries. They are also suitable for gasoline engines.

Features & Benefits

The key benefits of Mobil Delvac Super Multigrades include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

- Diesel-powered equipment from leading diesel engine manufacturers
- On highway light and heavy duty trucking
- Off highway industries including: trucking, construction, quarrying, and agriculture
- Mixed diesel/gasoline engine fleets

Specifications & Approvals

Mobil Delvac Super Multigrades are also recommended for use in applications requiring:	10W-30	15W-40	20W-50
API CF-4/SF/SG	X	X	X

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



Typical Properties

Mobil Delvac Super Multigrades			
SAE Grade	10W-30	15W-40	20W-50
Viscosity, ASTM D 445			
cSt @ 40°C	76	105	145
cSt @ 100°C	11.5	14.3	17.4
Viscosity Index, ASTM D 2270	146	139	132
Sulfated Ash, wt%, ASTM D 874	0.8	0.8	0.8
Total Base # , mg KOH/g, ASTM D 2896	8.2	8.2	8.2
Pour Point, °C, ASTM D 97	-33	-27	-30
Flash Point, °C, ASTM D 92	224	234	244
Density @ 15°C kg/l, ASTM D 4052	0.88	0.88	0.88

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

