

Mobilgard 12 Series



Diesel Engine Oils

Product Description

Mobilgard 12 Series by ExxonMobil are high performance diesel engine oils developed for use in trunk piston engines operating on low sulphur distillate fuels in marine and industrial applications. They are formulated to have excellent resistance to oxidation and viscosity increase over a long period of service. They have superior water separating properties and provide excellent corrosion protection.

Mobilgard 312 and 412 meet API requirements for CF rating.

Features & Benefits

Mobilgard 12 Series is formulated with base oils having proven successful performance in diesel engines. The additive system is balanced to provide excellent resistance to thermal degradation under moderately severe operating conditions. They also provide good engine cleanliness and superior wear protection.

When used as recommended, Mobilgard 12 Series oils provide the following features and potential benefits:

Features

Excellent thermal and oxidation stability

Improved antiwear properties

Excellent TBN reserve and retention

Excellent detergency/dispersancy properties

Advantages and Potential Benefits

Extended periods between inspections, overhaul and cleaning

Reduced ring and liner wear

Increased protection against corrosive wear

Increased oil service life
Cleaner engines

Applications

Mobilgard 12 Series diesel engine oils are intended for use as cylinder and bearing lubricants in marine and industrial diesel engines operating on distillate fuels or light fuel blends. They are particularly effective in small bore, high speed truck engines in fishing fleets; in new, severe service engines; and in many types of medium speed engines. They may be used as crankcase lubricants in large crosshead type diesel engines operating on high sulphur fuels. Mobilgard 512 is recommended occasionally by some builders as running-in oil for crosshead type engines.

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request through your sales contract office, or via the Internet on <http://www.exxonmobil.com>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Typical Properties

Mobilgard	312	412	512
SAE Grade	30	40	50
Specific Gravity at 15°C	0.896	0.899	0.903
Flash Point, °C, ASTM D 92	266	292	282
Pour Point, °C, ASTM D 97	-9	-9	-9
Viscosity, ASTM D 445			
cSt, at 40°C	108	142	219
cSt, at 100°C	12	14.5	19
Viscosity Index, ASTM D 2270	100	100	100
TBN, mg KOH/g, ASTM D 2896	15	15	15
Sulphated Ash, wt%, ASTM D 874	2.1	2.1	2.1

Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly.