

# Product Data Sheet

## Mobil Gearlube VS 600 Fully Synthetic Gear Oil for BMW Rear Axles

### Product Description and Application

Mobil Gearlube VS 600 is a fully synthetic, SAE 75W-90 rear axle oil for use in hypoid axles. It has excellent oxidation control and high temperature stability, high load carrying ability and resistance to foaming at high speed and high temperatures.

Mobil Gearlube VS 600 is specially formulated and approved by BMW for use in conventional (non-limited slip) differentials. It is also suitable for other high performance applications where an API GL-5 gear lubricant is specified.

### Benefits

Mobil Gearlube VS 600 offers the following benefits:

- Approved by BMW for use in rear axles
- Suitable for initial fill and service fill

### Specifications

Mobil Gearlube VS 600 meets the performance requirements of the API GL-5 specification.

## Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

## Typical Characteristics

---

	<b>Gearlube VS 600</b>
SAE Viscosity Grade	75W-90
Viscosity, cSt at 40°C	101
Viscosity, cSt at 100°C	15.4
Viscosity Index	161
Pour Point, °C	218
Flash Point, °C	-57

---

Due to continual product research and development, the information contained herein is subject to change without notice.

---

**Mobil Oil Company Limited**  
**Acting as Agent for Mobil Lubricants UK Limited**  
**ExxonMobil House, Ermyn Way**  
**Leatherhead, Surrey, KT22 8UX**  
**Telephone: 01372 22 2000**

