

Product Data Sheet

Mobilarma LT Dewatering, Long Term Corrosion Preventative

Product Description

Mobilarma LT is a high flash point solvent deposited, dewatering, long term corrosion preventative. It is an excellent general purpose rust preventative providing medium to long term protection of ferrous and alloy components.

Benefits

Mobilarma LT is based on specially selected high flash point solvents and components which offer the following benefits:

- Effective medium to long term protection
- Improved drainage
- Reduced evaporation loss from treatment tanks
- Safer working environment
- Reduced health and safety demands
- Reduced storage requirements

Application

Mobilarma LT is a general purpose rust preventative which provides medium to long term protection of ferrous and alloy components. It is especially suited for the protection, during storage, of many types of spares e.g. engine components, automotive parts as well as extruded and machined surfaces. The protective film is very effective against acidic and other aggressive atmospheres.

Mobilarma LT is best applied by dipping but it can be sprayed or brushed on. Where necessary it can be removed by hydrocarbon solvents or suitable alkaline cleaners.

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

Mobilarma LT

Relative Density 15/4 °C	0.82
Film Type	Waxy-grease film
Film Thickness, microns	8.0
Drying Time at 20°C	240 mins. (solvent free)
Coverage, m ² / litre	38
Non-volatile content, % wt	31
Flash Point COC °C, min.	62
Corrosion protection:	
indoors	24 months
covered outdoors	12 months
outdoors	6 months

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

