

Product Data Sheet

Mobilgrease XHP 221 Premium Lithium Complex Grease

Product Description

Mobilgrease XHP 221 is a premium lithium complex, extreme pressure grease intended for a wide variety of applications. It is based on a ISO VG 220 mineral oil and is a NLGI grade 1.

It is formulated to provide excellent high temperature performance with excellent adhesion, structural stability and resistance to water (wash out). This grease has a high level of chemical stability and offers excellent protection against rust, corrosion and wear, especially on axles, rings and bearings.

Mobilgrease XHP 221 does not contain lead, chlorine or nitrite.

Benefits

Mobilgrease XHP 221 offers the following benefits:

- Reduced downtime and maintenance costs because of high level of protection against wear, corrosion and oxidation combined with an exceptional degree of rust protection against acidic water
- High anti-wear and extreme pressure performance to be suitable for a wide range of bearing speeds
- Extended intervals between relubrication due to long product life even under severe operating conditions
- Excellent resistance to water washout and contamination

Application

Mobilgrease XHP 221 is a NLGI 1 multi-purpose grease recommended where good high temperature and anti-leakage are required. It is designed to resist to water washout, water ingress, corrosive environment (paper/sugar mills) and shocks and vibrations. The operating temperature range is -20 to 150°C.

This product provides a heavier lubricating film thickness while the NLGI 1 grade will ensure good low temperature performance and makes it suitable for centralised lubrication systems.

Health and Safety

Based on available toxicological information, it has been determined that this product poses no significant health risk when used and handled properly.

Details on handling, as well as health and safety information, can be found in the Material Safety Data Bulletin which can be obtained through Mobil Oil Company Ltd., by telephoning 01372 22 2000.

Typical physical characteristics are given in the table. These are intended as a guide to industry and are not necessarily manufacturing or marketing specifications.

Typical Characteristics

Mobilgrease XHP 221

	Test Method	
NLGI Grade	ASTM D217	1
Soap Type	-	Lithium Complex
Colour	Visual	Dark Blue
Penetration at 25°C, Worked	ASTM D217	325
Dropping Point, °C	ASTM D22	>260
Viscosity of Oil, cSt at 40°C	ASTM D445	220
4-Ball, Scar mm	ASTM D2266	0.5
4-Ball Weld, kg	ASTM D2596	315
Timken OK Load, kg	ASTM D2509	20
Rust Protection	IP 220 Mod.	
Distilled Water Washout Test		0-0
Acidic Water (pH = 4.5)		0-0

Due to continual product research and development, the information contained herein is subject to change without notice.

Mobil Oil Company Limited
Acting as Agent for Mobil Lubricants UK Limited
ExxonMobil House, Ermyn Way
Leatherhead, Surrey, KT22 8UX
Telephone: 01372 22 2000

